



## ProContain

ProContain products are designed for extreme applications where high structural integrity is required. All ProContain products feature a durable scrim reinforcement when added puncture and tear strength is required. Flexibility and cold weather resistance are key features allowing for a workable membrane in any environment. ProContain is designed for applications where chemical, UV stabilization, or oxidative resistance is required. ProContain, built to last in any environment.

## ProFlex

ProFlex products are designed as a flexible, durable membrane that features enhanced expansion and contraction properties. All ProFlex products are blown-film extruded LLDPE providing a material with impressive stretch capabilities for a wide variety of applications. The FlexLL series provides a premium solution for Above Ground Storage Tanks (AST). FlexLL is a co-extruded film that allows for various color combinations to fit any installation requirement. ProFlex SLL series can be either mono-layer or co-extruded for textured applications that require added slip resistant properties. All ProFlex products can be fabricated in-house to reduce installation time for end users.

## ProCoat

ProCoat products are offered as a cost effective, light weight solution for many applications. ProCoat products are extremely flexible in cold weather and can be fabricated in-house up to 90,000 sqft., allowing the customer to order a complete liner in one piece. ProCoat products are reinforced with HDPE tapes offering extremely high puncture and tear strength relative to material weight. ProCoat offers durability for many applications in oil and gas and can be fabricated to custom length's and width's.

## ProFelt

ProFelt products are non-woven geotextiles comprised of polypropylene or polyester. ProFelt products are designed for erosion and sediment stabilization for a variety of applications. Rolls are standard 15' x 300' and can also be per-fabricated to specific sizes in-house for ease of installation on larger jobs. ProFelt is commonly fabricated into pad liners for use in Above Ground Storage Tank (AST) applications.

## Applications

- **Secondary Containment**
  - Above Ground Frac Tanks
  - Frac Ponds
  - Wastewater Lagoons
  - Spill Containment
  - Remediation Pits
  - Agricultural Ponds
  - Tank Battery Liners
  - Frac Tank Liners
- 
- **Above Ground Frac Tanks**
  - Frac Ponds
  - Containment Pits
  - Wastewater Lagoons
  - Remediation Pits
  - Reserve Pits
  - Agricultural Ponds
  - Tank Battery Liners
  - Frac Tank Liners
- 
- **Reserve Pits**
  - Location Liners
  - Rig Mats
  - Secondary Containment
  - Tank Battery Liners
  - Frac Tank Liners
- 
- **AST Pads**
  - Erosion Control
  - Frac Pond Pads
  - Secondary Containment Pads



Formerly Western Industries, **Western ProLine** has over 30 years of experience in the liner fabrication business. Our manufacturing facilities can accommodate

nearly any size liner and a wide selection of materials. **Western ProLine** is committed to providing superior materials, quality fabrication, customer satisfaction and timely deliveries.

### ProContain - Secondary Containment

Product	Mil	Reinforced	Material
L25WC	25	HDPE Thread	LLDPE/HDPE/Polymer Film
L30WC	30	HDPE Thread	LLDPE/HDPE/Polymer Film
L24WCF	24	HDPE Thread	LLDPE/HDPE/3 oz. Felt
30RPE	30	Polyester	Polyethylene
36RPE	36	Polyester	Polyethylene
45RPE	45	Polyester	Polyethylene



### ProFlex - Tank Liner

Product	Mil	Reinforced	Material
Flex30LL	30	No	LLDPE Film
Flex40LL	40	No	LLDPE Film
20SLL	20	No	LLDPE Film
30SLL	30	No	LLDPE Film
30SLLT	30	No	LLDPE Film - Textured
40SLL	40	No	LLDPE Film
40SLLT	40	No	LLDPE Film - Textured



### ProCoat - Reserve Pit

Product	Mil	Reinforced	Material
WC12	12	HDPE Thread	LLDPE/HDPE/LLDPE
WC16	16	HDPE Thread	LLDPE/HDPE/LLDPE
WC20	20	HDPE Thread	LLDPE/HDPE/LLDPE
WC24	24	HDPE Thread	LLDPE/HDPE/LLDPE
WC30	30	HDPE Thread	LLDPE/HDPE/LLDPE



### ProFelt - Felt Liner

Product	Weight (oz.)	Material
PT8	8	Polyester
PT10	10	Polyester
PP8	8	Polypropylene
PP10	10	Polypropylene

